



NLS-MT65

PORTABLE DATA COLLECTOR

FEATURES

○ Rugged Construction

The NLS-MT65's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.2m drops to concrete.

○ Superior Barcode Reading Performance

When equipped with Newland's fifth-generation **UIMC**® technology, the new NLS-MT65 can decode even poorer quality barcodes, such as soiled or wrinkled labels, with ease

○ Heavily Customized Android

The value-added features of the NLS-MT65, including application protection and admin tool, seek to shore up Android's data security.

○ Diverse Functionalities

The NLS-MT65 offers 1D/2D/BT/Wi-Fi/4G/3G/GPS/Camera/NFC functionalities to meet various application needs.



2D Barcode



1D Barcode



Android



4"
Color
Screen



GPS



IP65



4G



WiFi

NLS-MT65

Performance

Processor	2.0GHz quad-core processor
Operating System	Android 11
Memory	3GB RAM, 32GB ROM
Interface	Micro USB 2.0, Battery charging over USB supported

Physical/Electrical

Dimensions (L×W×H)	166 ×73 ×26 mm
Weight	330g (including battery)
Display	4" WVGA (800×480) capacitive touch screen
Keypad	30 keys (side keys included) with backlight
Notification	Vibration, speaker and multi-color LEDs
Battery	3.7V, 3800mAh
Camera	8 megapixels, auto focus, with LED flashlight
GPS	GPS (AGPS), GLONASS
Expansion	Micro SD card (max. 128GB) slot
AC Adapter	Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz

Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-30°C to 70°C (-22°F to 158°F)
Humidity	5% to 95% (non-condensing)
Static Discharge	±15 kV (air discharge), ±8 kV (direct discharge)
Drop	1.2m drops to concrete (for six sides, one drop per side)
Sealing	IP65

Barcode Scanning

2D Scan Engine Laser aiming Mega-pixel	1D: Code128, Code 49, Code 16K, (GS128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC-A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, Codabar, Code93, Code 11, Plessey, MSI Plessey, RSS. 2D: Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data Matrix, DotCode.
--	---

Depth of Field

Depends on barcode type and environment	Code39 (20mil) 90mm-580mm; EAN13 (13mil) 45mm-380mm Code39 (5mil) 75mm-180mm; DM (10mil) 50mm-180mm PDF417 (6.7mil) 70mm-170mm; QR (15mil) 40mm-220mm
---	---

NFC

13.56MHz RFID	ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693
---------------	---

Wireless

WLAN RADIO	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz
WWAN RADIO	2G GSM (B2, B3, B5, B8) 3G WCDMA (B1, B2, B5, B8); CDMA2000 1X/ EV-DO Rev. A (BC0); TD-SCDMA (B34, B39) 4G TD-LTE (B38, B39, B40, B41) FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)
WPAN RADIO	Dual mode Bluetooth 5.0+BLE (Backward-compatible)

Optional Accessories

AC adapter, cable, charging cradle, 4-slot charger
--

Specifications are subject to change without notice.

2021/12/27

Version: V1.0

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlscan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd.,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw