

SRP-330III

3-inch Thermal POS Printer



Spec Sheet

Print Characteristics

Print Method
Direct Thermal
Print Speed
Up to 250 mm/sec
Print Resolution
SRP-330III: 180 dpi
SRP-332III: 203 dpi
Print Width
Up to 72 mm
Sensor
Paper End, Cover Open

Media Characteristics

Media Type
Receipt
Media Width
80 mm
Optional 58 mm
Media Roll Diameter
Up to 80 mm
Media Thickness
0.05 to 0.08 mm
Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)
145 x 195 x 146 mm (5.72 x 7.79 x 5.74 inch)
Weight
1.6 kg (3.52 lbs.)
Electrical
EnergyStar® Certified,
External Power Adapter 100-240 VAC,
50/60 Hz
Drawer Port
2 ports (Via Y-Type Adapter)

Performance Characteristics

Memory
128 MB SDRAM, 64 MB Flash
NV Image Memory
768 Kbytes (Mono)
Receive Buffer
4 Kbytes
User Define Buffer
12 Kbytes
Interface
① USB 2.0 FS + Ethernet + Serial
② USB 2.0 FS + Serial
③ USB 2.0 FS + Parallel
④ USB 2.0 FS + Dual Serial (KOR Only)

Environment Characteristics

Temperature
Operating: 0 to 40°C (32 to 104°F)
Storage: -20 to 60°C (-4 to 140°F)
Humidity
Operating: 10 to 80% RH
Storage: 10 to 90% RH

Software

Emulation
BXL/POS™
Driver/Utility
Windows® Driver, OPOS/JPOS Driver,
Linux/Mac® CUPS Driver,
Virtual COM USB/Ethernet Driver,
Utility Program, Network Auto Installer
Developer Tools
Android™/iOS®/Windows SDK, Linux SDK,
Xamarin SDK, Web Print SDK, Cordova Plugin,
MAUI SDK, Flutter™ Plugin,
React Native SDK
Design & Print
mPrint App (Android, iOS)

Fonts/Graphics/Symbologies

Character Size
Font A: 12 x 24, Font B: 9 x 17,
Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line
SRP-330III: Font A: 42, Font B, C: 56,
KOR, CHN, JPN: 21
SRP-332III: Font A: 48, Font B, C: 64,
KOR, CHN, JPN: 24
Character Sets
Alphanumeric: 95
Extended Graphics: 128 x 35 page
International: 32
Barcode Symbologies
1D: Coda Bar, Code39, Code93,
Code128, EAN-8, EAN-13, ITF, UPC-A,
UPC-E
2D: Data Matrix, PDF417, QR Code

Accessories/Supplies

Included in the Box
Paper, Cable Cover, AC/DC Adapter,
Power Cord, 2-inch Partition (58 mm),
USB A-B Cable 1.8 m
Options & Accessories
External Buzzer, B-Melodist,
Serial Cable (9-9/25-9 pin),
Parallel Cable